


# *Artificial Intelligence*

## Introduction

Marco Piastra


# *Artificial* Intelligence?



(from Wikipedia)

- [Descartes, R., *Discours de la Methode*, 1637]

“I had after this described the **reasonable soul**, and shown that *it could by no means be educed from the power of matter*, as the other things of which I had spoken, but that it must be expressly created; and that it is not sufficient that it be lodged in the human body exactly like a pilot in a ship, unless perhaps to move its members, but that it is necessary for it to be joined and united more closely to the body, in order to have sensations and appetites similar to ours, and thus constitute a real man” [English version from Project Gutenberg]




(from Wikipedia)

- [Crick, F., *The Astonishing Hypothesis*, 1994]

“You, your joys and your sorrows, your memories and your ambitions, your sense of personal identity and free will, are in fact no more than the behavior of a vast assembly of nerve cell and their associated molecules.”

Can machines think?



(from Wikipedia)

- [Searle, J. R., *Minds, Brain and Science*, 1986]

“Because we do not understand the brain very well we are constantly tempted to use the latest technology as a model for trying to understand it.

In my childhood we were always assured that the brain was a telephone switchboard (*‘What else could it be?’*).

I was amused to see that Sherrington, the great British neuroscientist, thought that the brain worked like a telegraph system. Freud often compared the brain to hydraulic and electro-magnetic systems. Leibniz compared it to a mill, and I am told some of the ancient Greeks thought the brain functions like a catapult.

At present, obviously, the metaphor is the digital computer.”

# Turing Machine (A. Turing, 1937)

- An abstract model of effective computation

A **tape**, made up of individual **cells**

Each cell contains a **symbol**, from a finite **alphabet**

A **read/write head**, which can move in each direction - one cell at time

A **state register** that keeps the current **state**, from a finite set

A **transition table**, i.e. a set of *entries* like this:

$$\{ \langle \text{current state}, \text{symbol read} \rangle \rightarrow \langle \text{next state}, \text{symbol written}, \text{move} \rangle \}$$



The **transition table** describes a *finite state machine*

Each *transition* is governed by the input symbol, the current state and the corresponding entry in the transition table

The next state is written into the state register

The output is written to the cell

Then the head moves (i.e. *left, right, none*)



# Turing Machine (A. Turing, 1937)

- An abstract model of effective computation

A **tape**, made up of individual **cells**

Each cell contains a **symbol**, from a finite **alphabet**

A **read/write head**, which can move in each direction - one cell at time

A **state register** that keeps the current **state**, from a finite set

A **transition table**, i.e. a set of *entries* like this:

{  $\langle \text{current state}, \text{symbol read} \rangle \rightarrow \langle \text{next state}, \text{symbol written}, \text{move} \rangle$  }

- What is the meaning of this?



The Turing Machine is a mathematical model of a physical computing device

*(It is very simple)*

Any given problem for which there is a Turing Machine that computes the solution is clearly computable by a physical machine


***Is the vice-versa also true?***

*(If a problem is computable by a physical machine, does it exist a Turing Machine for it?)*





# Church-Turing Thesis



*Caution: there is no such a thesis in the original writings of either author. Its formulation can be extrapolated from both. Hence the attribution (made by others)*

- A possible formulation (from Wikipedia):


*“Every ‘function which would naturally be regarded as computable’ can be computed by a Turing machine.”*

*The vagueness in the above sentence gives raise to different interpretations. One of these (though not entirely equivalent) is (from Wikipedia):*

*“Every ‘function that could be physically computed’ can be computed by a Turing machine.”*

Searle: “... At present, obviously, the metaphor is the digital computer.”

# Can machines think? (the Turing Test)



(from Wikipedia)

- Turing, A., *Computing Machinery and Intelligence*, 1950

“[The ‘imitation game’] is played with three people, a man (A), a woman (B), and an interrogator (C) who may be of either sex.

The interrogator stays in a room apart from the other two.

The object of the game for the interrogator is to determine which of the other two is the man and which is the woman.

He knows them by labels X and Y, and at the end of the game he says either ‘X is A and Y is B’ or ‘X is B and Y is A’

The interrogator is allowed to put **questions** to A and B. [...]

We now ask the question,

‘What will happen when a machine takes the part of A in this game?’

Will the interrogator decide wrongly as often when the game is played like this as he does when the game is played between a man and a woman?

These questions replace our original, ‘Can machines think?’ ”

Do answers, however partial,  
change the original question?

# Deep Blue

In 1945 A. Turing mentions playing chess as an example of intelligent human activity that some days machines could perform

In 1946 A. Turing defines the first *algorithm* for playing chess

In 1997 the *Deep Blue* system, made by IBM, beats the world chess champion Gary Kasparov



(from Wikipedia)

- **Deep Blue, 1997** [Campbell, M., Hoane, A. J., Hsu, F., 2001]
  - 30 standard CPUs (120Mhz) + 480 special-purpose CPUs ('chess search engines', each evaluating 2.5M moves per second)
  - Three-layered hardware architecture, 30 GB of RAM
  - Software written in C
  - Wide usage of a large database of recorded games played by grand masters
- Questions:
  - Is Deep Blue *intelligent*?
  - Does Deep Blue *perform* an intelligent human activity?


# Can machines play chess?

## ■ Programming a Computer for Playing Chess [Shannon, 1948]

Chess game statistics

More than  $10^{43}$  different legitimate chessboard configurations

More than  $10^{120}$  possible games



(from Wikipedia)

## Strategy A

It is based on an *evaluation function*  $f(P)$  defined for all possible, **final** positions:

+1 if the first player (i.e. the computer) wins, regardless;

0 if it is a draw, regardless;

-1 if the second player wins, regardless;

The machine computes backwards the values of  $f(P)$  of all possible, **non-final** positions starting from all possible **final** positions

The value assigned to each **non-final** position  $P$  is equal to the sum of  $f$  values of the **final** position which  $P$  may lead to

At each move, the computer chooses the move that leads to the position with the maximum value of  $f$


# Can machines play chess?

## ■ Programming a Computer for Playing Chess [Shannon, 1948]

Chess game statistics

More than  $10^{43}$  different legitimate chessboard configurations

More than  $10^{120}$  possible games



(from Wikipedia)

### Strategy A

It is based on an *evaluation function*  $f(P)$  defined for all possible, **final** positions:

+1 if the first player (i.e. the computer) wins, regardless;

0 if it is a draw, regardless;

-1 if the second player wins, regardless;

The machine computes backwards the values of  $f(P)$  of all possible, **non-final** positions starting from all possible **final** positions

The value assigned to each **non-final** position  $P$  is equal to the sum of  $f$  values of the **final** position which  $P$  may lead to

At each move, the computer chooses the move that leads to the position with the maximum value of  $f$

***This strategy is unfeasible, even with modern computers, as it entails exploring all possible games***


# Can machines play chess?

## ■ Programming a Computer for Playing Chess [Shannon, 1948]

Chess game statistics

More than  $10^{43}$  different legitimate chessboard configurations

More than  $10^{120}$  possible games



(from Wikipedia)

### Strategy A (***revised***)

Use an approximate evaluation function  $f^*(P)$  on all possible positions

Given the current position in the game, the machine *looks forward* by exploring all possible positions not farther away than  $k$  moves


The computer chooses the move with the MINIMAX method

# Can machines play chess?

- Programming a Computer for Playing Chess [Shannon, 1948]


## Strategy A (*revised*)

The computer chooses the move with the MINIMAX method



(from Wikipedia)

Minimax on a two-person game tree of 4 plies




(from Wikipedia)



# Can machines play chess?

## ■ Programming a Computer for Playing Chess [Shannon, 1948]

### Strategy A (*revised*)



(from Wikipedia)

In the game tree for chess, each node has an average *branching factor* of 30

The number of nodes in the game tree is  $O(b^d)$

$b$  is the average *branching factor*

$d$  is the *depth* (i.e. how far the exploration goes)

The complete game tree for ply 2 contains  $30^2$  (i.e. around  $10^3$ ) nodes

The complete game tree for ply 6 around  $10^9$  nodes

A computer that can evaluate  $10^6$  positions per second would take more than 16 minutes

A typical chess game has ply 80-90

Human master players are believed to have an equivalent *lookahead* of ply 30-40 and more (but without an explicit computation...)

Note: the MINIMAX method can be optimized (i.e. with *alpha-beta pruning*, see Wikipedia) so that it is possible to double the *depth* that can be explored in the same time


# Can machines play chess?

## ■ Programming a Computer for Playing Chess [Shannon, 1948]

Chess game statistics

More than  $10^{43}$  different legitimate chessboard configurations

More than  $10^{120}$  possible games



(from Wikipedia)

### Strategy A (revised)

Use an approximate evaluation function  $f^*(P)$  on all possible positions

Given the current position in the game, the machine *looks forward* by exploring all possible positions not farther away than  $k$  moves

The computer chooses the move with the MINIMAX method (see after)

### Strategy B

“A good human player examines only **a few selected variations** and carries these out to a reasonable stopping point”

Use two functions that evaluate the stability of a position  $P$  and to what extent a move  $M$  in a position  $P$  *is worth being examined* at all

In short: find *higher level* patterns

# Strategy A or Strategy B?

[Shannon, 1948]

Due to the high computational complexity of Strategy A,  
he foresees a progressive development of Strategy B

(i.e. something like “Computer can improve by emulating humans”)

How did it go, in reality?


- At the early stages of computer chess technology, Strategy B was preferred
- During the period 1959-1962 a first ‘credible’ player was developed (Kotok-McCarthy)  
(at the *beginner* level)
- In 1973 the developers of the soon-to-be world champion in computer chess players abandoned Strategy B in favor of Strategy A
- Since then, Strategy A – with significant improvements – dominates the scene  
This includes *Deep Blue* and all current top-ranking computers  
Excellent computer chess players (i.e. *grandmaster level*) are now available for smartphones

# Deep Blue


- **Deep Blue, 1997** [Campbell, M., Hoane, A. J., Hsu, F., 2001]
  - Great *lookahead* power
    - On the average, it could search ply 12.2 ply in three minutes
  - Dedicated hardware
    - Special evaluation primitives implemented in silicon
  - Hybrid dedicated machine: hardware + software
    - Software algorithms in C for standard CPUs, easily modified
    - Specialized processors for exploring the game tree
  - Massive parallelism
    - More than 500 processors for parallel exploration
  - Huge database of games by grand masters (humans)

(It was turned off at the end of the match)

- Same questions:
  - Is Deep Blue *intelligent*?
  - Does Deep Blue *perform* an intelligent human activity?



# DeepQA (a.k.a. "Watson")



(from Wikipedia)

- *Jeopardy!*: a quiz game

*Category: General Science*

**Clue:** When hit by electrons, a phosphor gives off electromagnetic energy in this form.

**Answer:** Light (or Photons)

*Category: Diplomatic Relations*

**Clue:** Of the four countries in the world that the United States does not have diplomatic relations with, the one that's farthest north.

**Answer:** North Korea

*Category: Rhyme Time*

**Clue:** It's where Pele stores his ball.

**Answer:** soccer locker

*Category: Lincoln Blogs*

**Clue:** Secretary Chase just submitted this to me for the third time; guess what, pal. This time I'm accepting it.

**Answer:** his resignation

# DeepQA (a.k.a. "Watson")

## ■ DeepQA, 2010 [Ferrucci, D., et al. 2010]

The Event (14-18/02/2011)

In a sequence of three "*Jeopardy!*" games, Watson beats in a very convincing way the all-times human champions

- Brad Rutter, winner of the highest amount of money
- Ken Jennings, winner of the longest string of games

*Jeopardy!*: a quiz game

In the real game, questions can also be about images, audio or video displays

DeepQA can only accept spoken text as input

Autonomous search, local memory

The rules of the challenge forbid connecting to Internet during the game:

DeepQA must use its local memory only

It does use Internet during training

Conventional hardware, massive parallelism

High Performance system, with 2880 standard CPUs (no specialized hardware required)

Linux SUSE ES 11, Software in Java and C++, with Apache Hadoop and Apache UIMA

(IBM expects a commercial return from Watson)




(from Wikipedia)

# DeepQA (a.k.a. "Watson")

- How does it work?

*Very little is known...*



(from Wikipedia)

(from [Ferrucci, D, et al. 2010])

## Processing stream

"They used nearly every trick in the book.." (from a video on YouTube)


## Several competing streams in parallel

Each stream scores a 'degree of confidence': the best answer is chosen, at the end

# DeepQA (a.k.a. "Watson")

- How does it work?

*Very little is known...*



Progressive, incremental training

Vast usage of *machine learning* techniques



(from Wikipedia)

(from [Ferrucci, D, et al. 2010])



# Is Watson intelligent?

## ■ “Does Watson Think?”

[D. Ferrucci, transcript from video

<http://www.ted.com/webcast/archive/event/ibmwatson>]

“Huh, hmm, what’s my favorite response on that?  
(Do submarines swim?)

[...]

I’d like to look at it as a sort of task-based view:

when you think of Watson playing Jeopardy!

it is acting like an intelligent Jeopardy! player,

if you deconstruct its intelligence

you’re gonna find lots of different algorithms

no one of them you would look at and say

“Wow! That’s really intelligent! It really understands the question!”

[...]

You have this holistic effect,


where it’s solving a problem that you formally think

that takes you *think*, to solve that problem, ...

Watson is doing it in a perhaps different way.

[...]

And I think ultimately of it as a tool, that helps humans solving problems... “



# *Artificial* Intelligence (a cautious approach)

# Artificial Intelligence

- A modern (*and cautious*) approach
  - “The study of computer-based tools that help humans solving problems which *they* think require intelligence”

# Artificial Intelligence

- A modern (*and cautious*) approach
  - “The study of computer-based tools that help humans solving problems which *they* think require intelligence”
  - “And which, from time to time, helps them understanding how their own intelligence actually works.”